

# MATERIAL SAFETY DATA SHEET

ASHLAND CHEMICAL COMPANY  
DIVISION OF ASHLAND OIL, INC.  
P.O. BOX 2219, COLUMBUS, OHIO 43215  
(614) 889-3333



24-HOUR EMERGENCY TELEPHONE (606) 324-1133

000175

HETRON 92

CODE DPM 754

PAGE: 1

ACCEPTED BY O.S.H.A. AS ESSENTIALLY SIMILIAR TO O.S.H.A. FORM 20

DPM 754

ASHLAND PRODUCT NAME: HETRON 92

CODE DPM 754

MCDONNELL-DOUGLAS CORPORATION  
AIRCRAFT DIVISION  
ACCOUNTS PAYABLE DEPT C1-102  
P O BOX 2731  
LONG BEACH CA 90808

03 56 041 5443200-  
DATA SHEET NO: 0027074-002  
LATEST REVISION DATE: 08/83-83223  
PRODUCT: 563101  
INVOICE: 086489  
INVOICE DATE: 12/14/84  
TO: MCDONNELL-DOUGLAS CORPORATION  
DEPARTMENT C-6-324P  
190TH & NORMANDIE  
TORRANCE CA 90501

ATTN: PLANT MGR./SAFETY DIR.

## SECTION I-PRODUCT IDENTIFICATION

GENERAL OR GENERIC ID: UNSATURATED POLYESTER RESIN

HAZARD CLASSIFICATION: (03) FLAMMABLE LIQUID (173.115)

## SECTION II-HAZARDOUS COMPONENTS

INGREDIENT	PERCENT	PEL	TLV
STYRENE	25-30	100	50 PPM

## SECTION III-PHYSICAL DATA

PROPERTY	REFINEMENT	MEASUREMENT
INITIAL BOILING POINT	FOR COMPONENT (25-30 %)	293.40 DEG F 145.22 DEG C 760.00 MMHG
VAPOR PRESSURE	FOR COMPONENT (25-30 %)	5.00 MMHG 68.00 DEG F 20.00 DEG C
VAPOR DENSITY		HEAVIER THAN AIR
SPECIFIC GRAVITY		1.320 - 1.344 77.00 DEG F 25.00 DEG C
PERCENT VOLATILES		30-35 %
EVAPORATION RATE		SLOWER THAN ETHER

## SECTION IV-FIRE AND EXPLOSION DATA

FLASH POINT 73-100 DEG F  
(23-28 DEG C)

EXPLOSIVE LIMIT (LOWEST VALUE OF COMPONENT) LOWER - 1.1%

EXTINGUISHING MEDIA: REGULAR FOAM OR WATER FOG OR CARBON DIOXIDE OR DRY CHEMICAL

HAZARDOUS DECOMPOSITION PRODUCTS: MAY FORM TOXIC MATERIALS: CARBON DIOXIDE AND CARBON MONOXIDE, HYDROGEN CHLORIDE, PHOSGENE

SPECIAL FIREFIGHTING PROCEDURES: WATER OR FOAM MAY CAUSE FROTHING WHICH CAN BE VIOLENT AND POSSIBLY ENDANGER THE LIFE OF THE FIREFIGHTER, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT, BURNING LIQUID.

SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

UNUSUAL FIRE & EXPLOSION HAZARDS: VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR MAY BE MOVED BY VENTILATION AND IGNITED BY PILOT LIGHTS, OTHER FLAMES, SPARKS, HEATERS, SMOKING, ELECTRIC MOTORS, STATIC DISCHARGE, OR OTHER IGNITION SOURCES AT LOCATIONS DISTANT FROM MATERIAL HANDLING POINT.

NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

## SECTION V-HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL: NOT ESTABLISHED FOR PRODUCT. SEE SECTION 15

EFFECTS OF OVEREXPOSURE: FOR COMPONENT


EYES - CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION.

SKIN - PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS.

BREATHING - EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS, AND EVEN ASPHYXIATION.

SWALLOWING - CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

FIRST AID:



MATERIAL SAFETY  
DATA SHEET

24-HOUR EMERGENCY TELEPHONE (606) 324-1133

000175

HETRON 92

CODE DPM 754

PAGE: 2

## SECTION V-HEALTH HAZARD DATA (CONTINUED)

- IF ON SKIN: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. LAUNDRY CONTAMINATED CLOTHING BEFORE RE-USE.
- IF IN EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION.
- IF SWALLOWED: DO NOT INDUCE VOMITING, KEEP PERSON WARM, QUIET, AND GET MEDICAL ATTENTION. ASPIRATION OF MATERIAL INTO THE LUNGS DUE TO VOMITING CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.
- IF BREATHED: IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

## SECTION VI-REACTIVITY DATA

- HAZARDOUS POLYMERIZATION: CAN OCCUR -- AVOID EXPOSURE TO EXCESSIVE HEAT, PEROXIDES AND POLYMERIZATION CATALYSTS.
- STABILITY: STABLE
- INCOMPATIBILITY: STRONG ALKALIES., STRONG MINERAL ACIDS.

## SECTION VII-SPILL OR LEAK PROCEDURES

## STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

- SMALL SPILL: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND TRANSFER TO HOOD.
- LARGE SPILL: ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES INCLUDING PILOT LIGHTS, ELECTRICAL SPARKS). PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN COMPLETED. STOP SPILL AT SOURCE, DIKE AREA OF SPILL TO PREVENT SPREADING, PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID MAY BE TAKEN UP ON SAND, CLAY, EARTH, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS.

## WASTE DISPOSAL METHOD:

- SMALL SPILL: DESTROY BY INCINERATION IN ACCORDANCE WITH APPLICABLE REGULATIONS.
- LARGE SPILL: DESTROY BY LIQUID INCINERATION WITH OFF-GAS SCRUBBER. CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

## SECTION VIII-PROTECTIVE EQUIPMENT TO BE USED

- RESPIRATORY PROTECTION: IF TLV OF THE PRODUCT OR ANY COMPONENT IS EXCEEDED, A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS UNDER SPECIFIED CONDITIONS. (SEE YOUR SAFETY EQUIPMENT SUPPLIER). ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.
- VENTILATION: PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).
- PROTECTIVE GLOVES: NEOPRENE, NITRILE RUBBER
- EYE PROTECTION: CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATIONS ARE ADVISED; HOWEVER, OSHA REGULATIONS ALSO PERMIT OTHER TYPE SAFETY GLASSES. (CONSULT YOUR SAFETY EQUIPMENT SUPPLIER)
- OTHER PROTECTIVE EQUIPMENT: NORMAL WORK CLOTHING COVERING ARMS AND LEGS.

## SECTION IX-SPECIAL PRECAUTIONS OR OTHER COMMENTS

- CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED.
- OVEREXPOSURE TO STYRENE HAS APPARENTLY BEEN FOUND TO CAUSE THE FOLLOWING EFFECTS IN LABORATORY ANIMALS: LIVER ABNORMALITIES, KIDNEY DAMAGE AND LUNG DAMAGE.
- THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH ASHLAND OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENTLY APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

